

tensid uk ltd

Product Data

AGS New Generation Graffi Clean 300®

Description and use

AGS Graffi Clean 300 is a viscous graffiti remover/paint stripper for use on masonry surfaces. It is a gelled remover which will cling to the surface.

Recommended as follows. Always test.

Substrate	Type		m ² per litre
Concrete		Yes	2 – 4
Marble Travertine Limestone	Polished	Yes	3 - 6
	Unpolished	Yes	2 – 5
Granite	Polished	Yes	3 – 6
	Unpolished	Yes	2 – 5
Sandstone	Unpolished	Yes	3 – 6
Slate	Unpolished	Yes	2 – 5
Fired Clay	Brick	Yes	2 – 4
	Tile	Yes	3 – 6
	Terracotta	Yes	3 – 6
	Pavers	Yes	3 - 6
Wood		Yes	

Advantages

- Fast acting and effective on most masonry surfaces

Limitations

- Not suitable for polycarbonate and some plastics

Preparation

Protect surrounding surfaces.

Equipment

Apply with a solvent resistant brush, airless sprayer or roller.

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Technical Data

Form: Gel
pH: N/A

Application Instructions

1. Apply with brush, airless sprayer or roller for large areas.
2. Leave to penetrate for 15 – 60 minutes. With low outside temperatures, longer dwell times may be necessary. Avoid applying to surface temperatures below 5°C.
3. Can be used on wet or damp surfaces.
4. Wash off with high pressure (60 – 150 bar, 10 – 20 litres per minute, depending on surfaces conditions), 90°C hot water will help removal.
5. If ghosting remains on the surface, use Graffi Ghost and Graffi Rinse.

Note: Never use higher pressure than the surface can tolerate. Extend penetration time when using lower pressure. High pressure washer with high flow rate of 15-30 litres per minute will also aid removal and compensate for lower pressure.

Coverage Rates

Coverage rates will vary according to the character of the surface.

Packing

4 x 5 litre plastic containers

Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bear skin or eyes. Always refer to material safety data sheet before use.

Technical Data

Does not contain aromatic hydro carbons

Shelf Life

Graffi Clean 300 may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to msds for full information before using this product.