

## SAFETY DATA SHEET GRAFFI COAT 103

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME                    GRAFFI COAT 103  
 PRODUCT NO.                    Base  
 SUPPLIER                        Tensid UK Ltd  
                                       Aquila House  
                                       70A Wheatash Road  
                                       Addlestone  
                                       Surrey  
                                       KT15 2ES  
                                       01932 564133

### 2 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45)        R43. R52/53.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate		41556-26-7	< 1%	N;R50/53. R43.
BUTYL ACETATE -norm	204-658-1	123-86-4	1-5%	R10 R66 R67
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		82919-37-7	< 1%	N;R50/53. R43.
Mix of a-3-(3-(2H-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)proplonyl-j-hydr		104810-48-2	1-5%	N;R51/53. R43.

The Full Text for all R-Phrases is Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Remove victim immediately from source of exposure. Get medical attention.

#### INGESTION

Get medical attention if any discomfort continues.

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

#### EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Foam, carbon dioxide or dry powder. Water spray.

#### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

#### SPECIFIC HAZARDS

Vapours/gases/fumes of: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

### 6 ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS

Aviod breathing vapours.

**GRAFFI COAT 103****ENVIRONMENTAL PRECAUTIONS**

DO NOT allow to enter drains or watercourses.

**SPILL CLEAN UP METHODS**

Absorb in vermiculite, dry sand or earth and place into containers.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS**

Keep containers tightly closed.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	

WEL = Workplace Exposure Limit.

**ENGINEERING MEASURES**

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

**HAND PROTECTION**

Use protective gloves. Polyvinyl chloride (PVC).

**EYE PROTECTION**

Wear approved safety goggles.

**OTHER PROTECTION**

Wear appropriate clothing to prevent repeated or prolonged skin contact.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid
COLOUR	Black
ODOUR	Characteristic

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Not known.

**11 TOXICOLOGICAL INFORMATION****GENERAL INFORMATION**

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

**12 ECOLOGICAL INFORMATION**

**GRAFFI COAT 103**

## ECOTOXICITY

Large quantities of the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

**13 DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

GENERAL This product is not classified as hazardous for transportation.  
UN NO. ROAD 1263

**15 REGULATORY INFORMATION**

## LABELLING



Irritant

CONTAINS Mix of a-3-(3-(2H-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)proplonyl-j-hydr

## RISK PHRASES

R43 May cause sensitisation by skin contact.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SAFETY PHRASES

S23 Do not breathe vapour/spray.  
S24 Avoid contact with skin.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.  
S51 Use only in well-ventilated areas.  
S60 This material and its container must be disposed of as hazardous waste.

**16 OTHER INFORMATION**

## GENERAL INFORMATION

Revised in accordance with CHIP 3

## REVISION COMMENTS

This is first issue.

SDS NO. 10856

## RISK PHRASES IN FULL

R10 Flammable.  
R43 May cause sensitisation by skin contact.  
R66 Repeated exposure may cause skin dryness or cracking.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67 Vapours may cause drowsiness and dizziness.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.