

tensid uk ltd

Product Data

Cladex LD

Description and use

Cladex LD is a pH neutral cleaning product formulated on the basis of surface active substances. Recommended for cleaning medium soiled plastic type surfaces, coated and painted surfaces. Also suitable for anodised aluminium and other types of metal based cladding materials.

Advantages

- Biodegradable
- Formulated to remove atmospheric soiling
- Ideal for maintenance cleaning
- User friendly formulation

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Technical Data

Description: Light yellow liquid
pH: 7

Application Conditions

Minimum air temperature 5⁰C
Maximum relative humidity 100%
Minimum surface temperature 5⁰C
Maximum surface temperature 30⁰C

Application Instructions

Initial cleaning: Depending upon level of soiling, maximum dilution 1:5

Maintenance cleaning: Maximum dilution 1:20

1. Apply the solution with a sponge or low pressure sprayer, leave for a few minutes, some agitation might be required.
2. Do not allow the product to dry on the surface.
3. Rinse thoroughly with clean water

N.B. For heavily soiled surfaces use Cladex HD.

Coverage Rates

Approximately 10m² per litre, depending upon the level of soiling.

Packing

1 x 10 litre plastic container

Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bear skin or eyes. Always refer to material safety data sheet before use.

Shelf Life

Cladex LD may be stored for a minimum of 12 months in a tightly sealed, unopened container. Store in an ambient temperature not below 0⁰C or above 30⁰C. Protect from frost.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to msds for full information before using this product.