

# tensid uk ltd

## Product Data

### AGS® Eeze Strip

#### Description and use

AGS Eeze Strip is a fast acting, high performance gelled paint stripper formulated to remove most paint types, urethanes and other coatings.

*Recommended as follows. Always test.*

Substrate	Type		m <sup>2</sup> per litre
Marble Travertine Limestone	Polished	Yes	1 – 2.5
	Unpolished	Yes	1 – 2.5
Granite	Polished	Yes	1 – 2.5
	Unpolished	Yes	1 – 2.5
Sandstone	Unpolished	Yes	1 – 2.5
Slate	Unpolished	Yes	1 – 2.5
Fired Clay	Brick Tile Terracotta Pavers	Yes	1 – 2.5
Concrete		Yes	1 – 2.5
Wood		Yes	1 – 2.5
Glass		Yes	1 – 2.5

#### Advantages

- Can be used for most paint types
- Fast acting
- Strips multiple layers of paint

#### Technical Data

Form:	White opaque viscous gel
pH:	7 - 8
Flash point:	N/A

#### Preparation

Protect surrounding surfaces and beware of wind drift.

#### Equipment

Apply with a chemical resistant brush.

#### Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

#### Application Instructions

1. Apply a uniform coating of Eeze Strip to the dry surface.
2. Allow the stripper to remain on the surface for 15 – 30 minutes, or until the coating shows indication of dissolving. Agitating with a stiff bristled brush will improve results.
3. Do not allow the product to dry on the surface.
4. Pressure rinse with water. Hot water may improve the efficiency of stripping. Alternatively, remove dissolved paint with a spatula and rinse area thoroughly with clean water.
5. Re-application may be necessary, but ensure surface is dry prior to application of Eeze strip.

#### Coverage Rates

Coverage rates will vary according to the character of the surface.

#### Packing

4 x 5 litres or 1 x 25 litre plastic container.

#### Safety Information

Wear suitable PPE – Nitrile impervious goggles and gloves to avoid splash to bear skin or eyes. Always refer to material safety data sheet before use.

#### Technical Data

Contains Methylene Chloride.

#### Shelf Life

AGS Eeze Strip may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to msds for full information before using this product.