

tensid uk ltd

Product Data

AGS Graffi Ghost Gel® Graffiti Remover

Description and use

AGS Graffi Ghost can be used following the initial graffiti removal with other AGS products, in cases where “ghosting” or shadowing remains on the surface. Graffi Ghost Gel is also in ideal cleaning agent for the removal of soot, grease and oil substances.

Recommended as follows. Always test.

Substrate	Type		m ² per litre
Concrete		Yes	3 - 8
Marble Travertine Limestone	Polished*	Yes	2 - 6
	Unpolished	Yes	3 - 8
Granite	Polished*	Yes	2 - 6
	Unpolished	Yes	3 - 8
Sandstone	Unpolished	Yes	3 - 8
Slate	Unpolished	Yes	2 - 5
Fired Clay	Brick	Yes	2 - 5
	Tile	Yes	2 - 5
	Terracotta	Yes	2 - 5
	Pavers	Yes	2 - 5
Wood		No	
Aluminium		No	

* Note: may damage some polished stone. Always test.

Advantages

- Fast acting and effective on most masonry surfaces
- Biodegradable

Technical Data

Form: Clear, yellow gel
pH: 14
Flash point: 70°C

Preparation

Protect surrounding surfaces and beware of wind drift.

Equipment

Apply with an alkaline resistant brush or low compression sprayer.

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Application Instructions

1. Brush apply Graffi Ghost Gel generously to the affected area, immediately after pressure washing so that the substrate is still damp.
2. Allow a dwell time of 5 to 20 minutes.
3. Rinse off with hot water (90°C) and as much pressure as the surface can tolerate.
4. If ghosting remains, repeat the process.
5. Use of Graffi Ghost Rinse will help neutralise the surface thoroughly. (Please refer to data sheet).

Coverage Rates

Coverage rates will vary according to the character of the surface.

Packing

4 x 5 litre plastic containers

Safety Information

Strongly corrosive. Wear suitable PPE – goggles and gloves to avoid splash to bear skin or eyes. Always refer to material safety data sheet before use.

Technical Data

Contains Potassium Hydroxide.

Shelf Life

Graffi Ghost Gel may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to msds for full information before using this product.