

Tensid uk plc

Product Data

AGS Graffi Ghost® Graffiti Remover

Description and use

AGS Graffi Ghost can be used following the initial graffiti removal with other AGS products, in cases where “ghosting” or shadowing remains on the surface.

Recommended as follows. Always test.

| Substrate | Type | | m ² per litre |
|-----------------------------------|------------|-----|--------------------------|
| Concrete | | Yes | 3 - 8 |
| Marble Travertine Limestone | Polished* | Yes | 3 - 8 |
| | Unpolished | Yes | 3 - 8 |
| Granite | Polished* | Yes | 3 - 8 |
| | Unpolished | Yes | 3 - 8 |
| Sandstone | Unpolished | Yes | 3 - 8 |
| Slate | Unpolished | Yes | 3 - 8 |
| Fired Clay | Brick | Yes | 3 - 8 |
| | Tile | Yes | 3 - 8 |
| | Terracotta | Yes | 3 - 8 |
| | Pavers | Yes | 3 - 8 |
| Wood | | No | |

* Note: may damage some polished stone. Always test.

Advantages

- Fast acting and effective on most masonry surfaces
- Biodegradable

Technical Data

Form: Clear, yellow liquid
Specific Gravity:
pH: 14
Flash point: 70°C

Preparation

Protect surrounding surfaces and beware of wind drift.

Equipment

Apply with an alkaline resistant brush or low compression sprayer.

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Application Instructions

1. Spray or brush apply Graffi Ghost generously to the affected area, immediately after pressure washing so that the substrate is still damp.
2. Allow a minimum dwell time of 3 to 5 minutes.
3. Rinse off with hot water pressure washer.
4. If ghosting remains, repeat the process.
5. Neutralise the surface with Graffi Ghost Rinse, and rinse well. (Please refer to data sheet).

Coverage Rates

Coverage rates will vary according to the character of the surface.

Packing

4 x 5 litre plastic containers

Safety Information

Strongly corrosive. Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

Technical Data

Contains Potassium Hydroxide.

Shelf Life

Graffi Ghost may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to msds for full information before using this product.