

tensid uk ltd

Product Data

Nano Xtreme Anti Graffiti Coating

Description and use

Nano Xtreme is a high performance specially developed coating which provides a gloss, hard scratch and wear resistant surface. Nano Xtreme is an anti graffiti coating which also provides an easy clean surface. Nano Xtreme is a single pack coating based on a polysilazane.

Nano Xtreme is for use on non porous surfaces such as cladding, stainless steel, clear coated and anodized aluminium, brass, copper, epoxy resin and painted surfaces.

Advantages

- Non yellowing
- Dirt repellent
- Hard, scratch and wear resistant
- Anti graffiti
- Excellent adhesive properties

Limitations

- Not suitable for brick or natural stone
- Not suitable for plastics
- May not be suitable for some water based paints
- Masonry and emulsion painted surfaces must first be primed with Graffi Coat 102

Technical Data

Form:	Colourless liquid
Odour:	Light ammonia
Flash point:	16°C

Preparation

Protect surrounding surfaces and beware of wind drift.

Equipment

Apply by wiping or spraying.

Application Instructions

1. Clean the surface carefully with alcohol or thinner.
2. The surface must be completely clean and dry.
3. Apply a small amount of Nano Xtreme to the surface sparingly with a dust free cloth.
4. Coverage is approximately 60 to 80 m² per litre.
5. Surface is touch dry after one hour.
6. Completely cured after one week.

Tools

Clean tools with alcohol or caustic potash solution.

Graffiti Removal

Remove graffiti using Graffi Green – see separate data sheets.

Coverage Rates

Coverage rates are between 60 and 80 m² per litre.

Packing

1 litre containers.

Shelf Life

Nano Xtreme may be stored for up to 1 year in an unopened container and at ambient temperature.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to msds for full information before using this product.

Aquila House, 70a Wheatash Road, Addlestone, Surrey KT15 2ES

T: 01932 564133 F: 01932 562046 E: info@tensid.com W: www.tensid.com